



BORMA WACHS®

Technical Informations

SHELLAC SANDING SEALER



Description

Shellac Sanding Sealer is transparent shellac based, of the highest quality.

Produced with natural shellac wax, and given its transparency, it is ideal as a first coat in the treatment of wax or shellac on light wood such as pine etc....

Completely formulated with natural products, and ready to use, it is fast drying and of notably adhesion.

Physical & chemical characteristics

Appearance:	liquid
Colour:	colourless (lightly golden)
Odour:	characteristic
Dilution:	ready to use
Possible dilution :	10 - 20 % ethylic alcohol
Drying process:	2 / 3 hrs at 20° C
Dry residue:	30 %
Specific weight:	0,83 + 0,03
Yield:	9 /12 mq x LT

Method of usage

Spread with the aid of a brush and wait until it is completely dry.

After the first coat, a second application is advisable, after the surface is perfectly dried and lightly sandpapered, with a fine grain min. 240.

After, preferentially two coats, the product allows a very easy brilliant result with wax polishes or shellac polishes.

Storage

The product must be stored, handled and used within the standards of hygiene and safety industrial practice.

Package

The product is packed in cans of 500ml, 1 litre and 5 litres.

Attention

Our technical sheets are compiled on the bases of results of our tests. Nevertheless our technical advise is in good faith, but without a guarantee. Indeed different supports, conditions, applications, installations, dilutions are integrating parts of the final result and often beyond every control. The user must test the supplied products to verify if it is adaptable for his/her needs.

We can guarantee the continuity of the physical and chemical characteristics.